

Fire Vulcan® LED Rechargeable Lantern



Case Material: High-impact ABS thermoplastic housing with rubberized cushioned-grip handle.

Dimensions: Length: 7.50 in. (19.05 cm) Width: 5 in. (12.7 cm) Height: 6.50 in. (16.51 cm)

Weight: 1.85 lbs (839 grams) with battery

Light Source: C4 LED technology, impervious to shock with a 50,000 hour lifetime.
Two (2) ultra bright blue LEDs.

Light Output: High: 80,000 candela peak beam intensity; 145 lumens
Low: 40,000 candela peak beam intensity; 70 lumens
Deep-dish parabolic reflector produces a tight beam with optimum peripheral illumination to aid in navigation. Optimized electronics provide regulated intensity.



Battery/Run Time: Two (2) lightweight Lithium-Ion nanotechnology cells. Recharges in 5 hrs.
Steady High LED & tail lights: Up to 3 hours of runtime to the 10% output level.
Steady Low LED & tail lights: Up to 7 hours of runtime to the 10% output level.
Steady High LED only: Up to 3.5 hours of runtime to the 10% output level.
Blinking High LED only: Up to 5 Hours of runtime to the 10% output level.
Blinking tail lights only: Up to 20 hours of runtime.

On/Off Push and hold momentary toggle switch to access 8 Modes of operation.

Left Modes:

(Optional Programmable 2, 3 or 4)

1-Steady High LED/Steady tail lights

2-Steady Low LED/Steady tail lights

3-Steady High LED/No tail lights

4-No LED/Steady tail lights

Right Modes:

(Optional Programmable 2, 3 or 4)

1-Steady High LED/Blinking tail lights

2-Steady Low LED/Blinking tail lights

3-Blinking High LED/No tail lights

4-No LED/Blinking tail lights

Models: Standard System - Includes quick release buckle strap, charging rack and both AC and DC chargers.

Vehicle Mount System - Includes quick release buckle strap and 12V DC vehicle-mountable direct wire charging rack.

Features: IPX7 Rated design (1 meter for 30 minutes). Lantern floats.
Ultra lightweight at 1.85 lbs.
LED Solid State circuitry provides regulated light output throughout battery life.
Serialized for positive identification.
Fits existing Streamlight Vulcan chargers.

Approvals**: Class I Division 2 Groups A, B, C, D, Temperature T4A;
Class II Division 2 Groups F, G, Class III, Temperature T-54°C (T6)
Most models meet applicable European Community Directives.
Rack meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position.

Warranty: Limited lifetime warranty.

**With battery (included in purchase).
Designed and Assembled In The USA.*

Item	UPC	Part #
Fire Vulcan LED Standard System 120V w/ quick release shoulder strap. AC/DC. Orange	080926-44450-8	44450
Fire Vulcan LED Vehicle Mount System 12V w/ quick release shoulder strap. DC. Orange	080926-44451-5	44451
Fire Vulcan LED Standard System 230V w/ quick release shoulder strap AC/DC Orange	080926-44452-2	44452
Fire Vulcan LED Standard System 240V w/ quick release shoulder strap AC/DC Orange	080926-44453-9	44453
Fire Vulcan LED Standard System 100V w/ quick release shoulder strap AC/DC Orange	080926-44455-3	44455
Fire Vulcan (WITHOUT CHARGER) w/ quick release shoulder strap. Orange	080926-44454-6	44454
<i>See reverse side for additional part numbers</i>		





Item	UPC	Part #
DC2 direct wire charge cord	080926-22050-8	22050
DC1 Charge Cord	080926-22051-5	22051
120V AC charge cord	080926-22311-0	22311
Battery <i>(not shown)</i>	080926-44610-6	44610
Quick Release Strap	080926-44050-0	44050
Charging Rack - Orange <i>(not shown)</i>	080926-44101-9	44101
Direct Wire 12V DC Mounting Rack - Orange <i>(not shown)</i>	080926-44131-6	44131
Shoulder Strap	080926-45232-9	45232